thermo scientific



Thermo Scientific Revco RDE Series -40°C Ultra-Low Temperature Freezers



- H-drive hydrocarbon refrigeration system provides sustainable performance with reliability you can count on
- Low peak variation helps ensure sample temperature protection throughout entire cabinet
- Fast door opening recovery in as little as 18 minutes
- Long warm-up time from -40°C to -20°C in up to 6 hours
- Three capacities: 400, 500 and 600 2-inch boxes
- Decrease storage footprint up to 25%
- 5-year standard warranty



Designed to keep your samples safe

- Worry-free storage; with low peak variation, samples are protected throughout the entire cabinet.¹
- Secure freezer settings with sample security
- Backed by our Global Service and Support Team

Limit environmental impact and lower HVAC costs

- Uses as low as 4.4 kWh/day, depending on size
- Less heat emission lowers HVAC costs
- Natural refrigerants compliant with EU F-Gas regulation: R290
- Environmentally-friendly, water-blown foam insulation
- Manufactured in an award-winning, zero-waste-to-landfill facility

User-friendly and quiet

- New HIC touch screen
 user interface
- Quiet enough to reside directly in the laboratory; at just 48 dBA, the sound is comparable to a home refrigerator.²

2. All data based on internal data unless otherwise noted. Data on file.


Typical freezer data based on internal testing with freezer setpoint at -80°C and ambient temperature at 20°C. Performance data varies across freezer size and electrical specifications.

Dependable storage with operational savings and sustainability

User-friendly HIC interface and cabinet

- Easy to use: plug in and go; no setup required
- H-drive Information Center (HIC) combines easy-to-read temperature with simple capacitive touch buttons
- Advanced security features: alarm settings, setpoint security passcode, and padlock-compatible doors
- Egonomic design: single-hand door operation, eye-level display, and shelf-level placement that do not require floor-level loading of racks
- Five inner doors minimize ambient temperature during sample retrieval

Specifications & Ordering Information





Upright Freezers (-10°C to -40°C)

General	Сар	acity		Amps / Breaker	Max Shelf	Interior Dimensions	Exterior Dimensions	Shipping
Purpose Model	Liters	Cryoboxes 5 cm	Electrical	(Plug type)	Weight kg	H x W x D cm	H x W* x D cm	Weight kg
RDE40040FD		400	208-230V/60Hz	3.4/15 (NEMA 6-15)	75	100 1 50 0 71 0	198.1 x 71.9 x 97.7	292
RDE40040FV	549	400	230V/50Hz	3.2/10 (European)		130.1 x 58.8 x 71.9	190.1 X / 1.9 X 9/./	292
RDE50040FD	000	500	208-230V/60Hz	4.0/15 (NEMA 6-15)	00	100 1 70 0 71 0	100 1 00 4 07 7**	004
RDE50040FV	682	500	230V/50Hz	3.4/10 (European)	93	130.1 x 73.0 x 71.9	198.1 x 86.4 x 97.7**	304
RDE60040FD	010	000	208-230V/60Hz	4.0/15 (NEMA 6-15)		100 1 07 0 71 0	100 1 100 0 07 7**	0.40
816 RDE60040FV		600	230V/50Hz	3.4/10 (European)	111	130.1 x 87.3 x 71.9	198.1 x 100.6 x 97.7**	348

*Allowance for handle and hinge, add 10.7 cm to cabinet width

**Doorway width clearance is 87.6 cm for RDE50040 and RDE60040



Performance Data

General Purpose Model	Energy Consumption* (kW-hr/day)	Peak Variation from -40°C Setpoint (°C)**	1-min Door Opening Recovery to -38.5°C (min)***	Warm-Up Time (-40°C to -20°C) (min)****	Sound (dBA)
RDE40040FD	4.4	+3.4 / -1.5	18	314	52
RDE40040FV	4.4	+3.2 / -1.6	19	309	51
RDE50040FD	5.1	+2.2 / -2.2	25	318	48
RDE50040FV	5.3	+1.8 / -2.2	22	328	51
RDE60040FD	5.9	+1.5 / -1.9	25	362	49
RDE60040FV	6.2	+1.7 / -1.9	29	339	48

*Energy Consumption: Typical data - internal testing with freezer setpoint at -40°C and 20°C ambient temperature

**Peak Variation from Setpoint: Typical data - internal testing with freezer setpoint at -40°C and 20°C ambient temperature

Door opening recovery: Typical data - internal recovery testing is to -38.5°C. During the door opening all inner and outer doors are opened for 60 seconds. *Warm Up Time: Typical data - internal testing with empty freezer setpoint at -40°C and ambient temperature at 20°

For specific model performance data, please refer to the individual technical specification sheet for the desired model.

Options (Field installations must be performed by a qualified professional)

			For Model Series			
Description	Installation	RDE40040	RDE50040	RDE60040		
	Factory	LN4567	LN4567	LN4567		
LN ₂ Backup System Maintains temperature down to -80°C with liquid nitrogen.	Field	FLN456LED* FLN456LEV**	FLN456LED* FLN456LEV**	FLN456LED* FLN456LEV**		
CO Backup Suptom	Factory	CO4567	CO4567	CO4567		
CO₂ Backup System Maintains temperature down to -67°C with CO ₂ .	Field	FCO456LED* FCO456LEV**	FCO456LED* FCO456LEV**	FCO456LED* FCO456LEV**		
Chart Recorder (Inkless) Seven-day inkless recorder	Factory	N/A	CR4567	CR4567		
Range: -115° to +50°C (+5°C resolution) Dia.: 6" (15.2 cm)	Field	N/A	FCR500LE	FCR600LE		
Chart Recorder (Ink)	Factory	N/A	CRP4567	CRP4567		
Seven-day ink recorder Range: -100° to +38°C (+2°C resolution) Dia.: 6" (15.2 cm) Models for RDE40040 are stand alone.	Field	6383-6D* 6383-6V** 6383-6W***	FCRP500LE	FCRP600LE		
Stainless Steel Freezer Interior	Factory	SS34567	SS34567	SS34567		
Twist Lock Plug NEMA L6-15P for 208-230V/60Hz	Factory	US230V15ATL	US230V15ATL	US230V15ATL		
I WIST LUCK FILLY NEIVIA LO-13P 101 200-2300/00HZ	Field	TL230V15A	TL230V15A	TL230V15A		
Twint Look Dive NEMA L6 20D for 200 2201//601-	Factory	US230V20ATL	US230V20ATL	US230V20ATL		
Twist Lock Plug NEMA L6-20P for 208-230V/60Hz	Field	TL230V20A	TL230V20A	TL230V20A		

* D = 208-230V/60Hz (NEMA 6-15 plug)

**V = 230V/50Hz (European plug)

***W = 230V/50Hz (UK plug)

Accessories

	For Model Series			
Description	RDE40040	RDE50040	RDE60040	
Air Filter (Replacement)	AF34567LE	AF34567LE	AF34567LE	
Alarm Delay Module Eliminates nuisance alarms due to intermittent or transitory conditions. (The alarm conditions must exist for a user-defined period before the signal is broadcast.)	6903	6903	6903	
Battery Backup (Replacement)	400159	400159	400159	
Chart Paper, for Inkless Recorder, 50/Pack	N/A	6185	6185	
Chart Paper, for Ink Recorder, 50/Pack	17020	17020	17020	
Cryo Gloves, Medium	4425	4425	4425	
Cryo Gloves, Large	4426	4426	4426	
Seismic Restraint Kits	TF-ULT400	TF-ULT500	TF-ULT600	
Shelf Kits: Include One Shelf and Clips	SK400	SK500	SK600	

Racks for Boxes and Microplates

Racks for 5 cm Boxes

Catalog No.	Description	Dimensions	Storage	For Model Series		
Catalog No.	Description	H x W x D cm	Capacities	RDE40040	RDE50040	RDE60040
		24 x 14 x 68.3	Boxes/Rack	20	20	20
398329	Sliding Drawer Rack		Racks/Shelf	4	5	6
390329			Racks/Freezer	20	25	30
			Boxes/Freezer	400	500	600
			Boxes/Rack	20	20	20
1950518	Adjustable Side Access Rack	23.9 x 13.7 x 67.9	Racks/Shelf	4	5	6
1950518			Racks/Freezer	20	25	30
Ann			Boxes/Freezer	400	500	600

Racks for 7.62 cm Boxes

Catalog No.	Description	Dimensions	Storage	For Model Series		
Catalog No.	Description	H x W x D cm	capacities	RDE40040	RDE50040	RDE60040
		24 x 14 x 68.3	Boxes/Rack	15	15	15
398328	Sliding Drawer Rack		Racks/Shelf	4	5	6
390320			Racks/Freezer	20	25	30
			Boxes/Freezer	300	375	450
			Boxes/Rack	15	15	15
1950519	Adjustable	00.010.707.0	Racks/Shelf	4	5	6
1950519	SideAccess Rack for 3 in. boxes	23.9 x 13.7 x 67.9	Racks/Freezer	20	25	30
And a second			Boxes/Freezer	300	375	450

Racking Shelf Kits

	Storage	For Model Series			
Description	Capacities	RDE40040	RDE50040	RDE60040	
	Catalog No.	RSK400SD5	RSK500SD5	RSK600SD5	
Sliding Drawer Racks with Boxes for One Shelf (12.7 x 12.7 x 5 cm Boxes with	Racks Included	5	6	6	
100-Count Cell Dividers)	Boxes Included	100	120	120	

Racks for Standard or Deepwell Microplates

	Description	Dimensions	Storage	For Model Series			
Catalog No.	Description	H x W x D cm	Capacities	RDE40040	RDE50040	RDE60040	
			Plates/Rack	98	98	98	
398322	Side Access Rack with	23.9 x 14 x 65.3	Racks/Shelf	4	5	6	
390322	Locking Rod	23.9 X 14 X 03.3	Racks/Freezer	20	25	30	
Applied and an applied a standard and a filling of the standard and a stan			Plates/Freezer	1960	2450	2940	
	Side Access Microplate Rack	23.9 x 14 x 64.8	Plates/Rack	77	77	77	
1050500			Racks/Shelf	4	5	6	
1950522			Racks/Freezer	20	25	30	
and a second			Plates/Freezer	1540	1925	2310	
			Plates/Rack	28	28	28	
	Sliding Drawer	00.0 14 05.0	Racks/Shelf	4	5	6	
1950639	Microplate Rack	23.9 x 14 x 65.3	Racks/Freezer	20	25	30	
			Plates/Freezer	560	700	840	

Boxes and Dividers

Catalog No.	Description	# of Dividers	Quantity	Color
5026-0909	Thermo Scientific [™] Nalgene [™] polycarbonate 5.08cm box for 1.2 to 2 mL vials	81	24/Case	White
5954	5.08 cm Fiberboard Box	0	12/Pack	White
820002	5.08 cm Fiberboard Box	81	1	White
820109	5.08 cm Fiberboard Box	100	1	White
5956	7.62 cm Fiberboard Box	0	12/Pack	White
820003	7.62 cm Fiberboard Box	81	1	White
1950878	5.08 cm Fiberboard Box	0	12/Pack	Multiple
1950879	5.08 cm Fiberboard Box	0	12/Pack	Pink
1950880	5.08 cm Fiberboard Box	0	12/Pack	Red
1950881	5.08 cm Fiberboard Box	0	12/Pack	Yellow
1950882	5.08 cm Fiberboard Box	0	12/Pack	Green
1950883	5.08 cm Fiberboard Box	0	12/Pack	Blue
1950884	5.08 cm Fiberboard Box	0	12/Pack	Black

Fiberboard Dividers

Catalog No.	Description	Quantity/Pack
5958	Grid Dividers, Hold 100 x 12 mm Tubes/Vials	12
6212	Grid Dividers, Hold 81 x 13 mm Tubes/Vials	12
5960	Grid Dividers, Hold 64 x 14 mm Tubes/Vials	12
5959	Grid Dividers, Hold 49 x 16 mm Tubes/Vials	12

Catalog No.	Description	Quantity
377267	Thermo Scientific™ Nunc™ 1.8 mL Screw-Top Round-Bottom Vials with Internal Threading	1,800/Case

Sliding Drawer Racks for Matrix and Cryobank Tubes

Racks work with all Thermo Scientific[™] Matrix[™] and Nunc[™] Cryobank Tubes

		For Model Series	RDE40040	RDE50040	RDE60040
200 µL Ca	pacity Tubes				
		Rack Model No.	1950786	1950786	1950786
	Matrix 200 µL 2D	Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
3747, 3748,	Internally Threaded Universal Tubes	Tubes/Box	96	96	96
4988	Box Dimensions:	Boxes/Rack	42	42	42
	8.5 x 12.8 x 2.75 cm	Racks/Shelf	4	5	6
		Racks/Freezer	20	25	30
		Tubes/Freezer	80,640	100,800	120,960
500 µL Ca	pacity Tubes				
	Matrix 500 ul. 2D	Rack Model No.	1950786	1950786	1950786
Box Dimensior	Open Top Tubes Box Dimensions: 8.5 x 12.8 x 2.6 cm	Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
3736, 3737,	Matrix 200 µL 2D Internally Threaded Universal Tubes with Installed DuraSeal™ Seal	Tubes/Box	96	96	96
4899	Box Dimensions: 8.5 x 12.8 x 2.75 cm	Boxes/Rack	42	42	42
374086,	Nunc Cryobank	Racks/Shelf	4	5	6
374087 (including	500 µL Internally Threaded Tubes	Racks/Freezer	20	25	30
color options)	Box Dimensions: 8.5 x 12.8 x 3.5 cm	Tubes/Freezer	80,640	100,800	120,960
		Rack Model No.	1950639	1950639	1950639
3743, 3744, 3745 (including color options)	Matrix 500 µL 2D	Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
	Internally Threaded ScrewTop Tubes	Tubes/Box	96	96	96
	Box Dimensions: 8.5 x 12.8 x 4.4 cm	Boxes/Rack	28	28	28
		Racks/Shelf	4	5	6
		Racks/Freezer	20	25	30
		Tubes/Freezer	53,760	67,200	80,640

Racks work with all Thermo Scientific[™] Matrix[™] and Nunc[™] Cryobank Tubes

		For Model Series	RDE40040	RDE50040	RDE60040
750 µL Cap	pacity Tubes				
		Rack Model No.	1950639	1950639	1950639
3731, 3732, 4896	Matrix 750 μL 2D Open Top Tubes Box Dimensions: 8.5 x 12.8 x 3.9 cm	Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
3729, 4896	Matrix 750 µL 2D Tubes with Installed DuraSeal Seal Box Dimensions: 8.5 x 12.8 x 3.9 cm	Tubes/Box	96	96	96
		Boxes/Rack	28	28	28
		Racks/Shelf	4	5	6
		Racks/Freezer	20	25	30
		Tubes/Freezer	53,760	67,200	80,640
1 mL Cap	acity Tubes				
		Rack Model No.	1950639	1950639	1950639
374088, 374089 (including color	Nunc Cryobank 1 mL Internally Threaded Tubes Box Dimensions: 8.5 x 12.8 x 4.9 cm	Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
		Tubes/Box	96	96	96
		Boxes/Rack	28	28	28
options)		Racks/Shelf	4	5	6
		Racks/Freezer	20	25	30
		Tubes/Freezer	53,760	67,200	80,640
3740, 3741, 3742 (including color options)	Matrix 1 mL 2D Internally Threaded Screw Top Tubes Box Dimensions: 8.5 x 12.8 x 5.8 cm	Rack Model No.	1950798	1950798	1950798
		Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
		Tubes/Box	96	96	96
		Boxes/Rack	21	21	21
		Racks/Shelf	4	5	6
		Racks/Freezer	20	25	30
		Tubes/Freezer	40,320	50,400	60,480

thermo scientific

Sliding Drawer Racks for Matrix and Cryobank Tubes

Racks work with all Thermo Scientific[™] Matrix[™] and Nunc[™] Cryobank Tubes

		For Model Series	RDE40040	RDE50040	RDE60040
1.4 mL Ca	pacity Tubes				
		Rack Model No.	1950639	1950639	1950639
3791, 3792, 4890	Matrix 1.4 mL 2D Open Top Tubes Box Dimensions: 8.5 x 12.8 x 4.9 cm	Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
3801, 4890	Matrix 1.4 mL 2D Tubes with Installed DuraSeal Seal Box Dimensions: 8.5 x 12.8 x 4.9 cm	Tubes/Box	96	96	96
		Boxes/Rack	28	28	28
3711, 3112, 4890	Matrix 1.4 mL Human Readable Open Top Tubes Box Dimensions: 8.5 x 12.8 x 4.9 cm	Racks/Shelf	4	5	6
		Racks/Freezer	20	25	30
		Tubes/Freezer	53,760	67,200	80,640
1.8 to 2 ml	L Capacity Tubes				
374500, 374501	Nunc 1.8 mL Externally Threaded Universal Tubes Box Dimensions: 8.5 x 12.8 x 5.5 cm	Rack Model No.	1950639	1950639	1950639
		Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
374221, 374223	Nunc Cryobank 2 mL Internally Threaded Tubes Box Dimension: 8.5 x 12.8 x 5.5 cm	Tubes/Box	48	48	48
		Boxes/Rack	28	28	28
		Racks/Shelf	4	5	6
01 1220		Racks/Freezer	20	25	30
		Tubes/Freezer	26,880	33,600	40,320
5 mL Cap	acity Tubes				
374220, 374222	Nunc Cryobank 5 mL Internally Threaded Tubes Box Dimensions: 8.5 x 12.8 x 9.6 cm	Rack Model No.	1950818	1950818	1950818
		Freezer Rack Dimensions W x H x D	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm	14 x 24 x 68.5 cm
		Tubes/Box	48	48	48
		Boxes/Rack	14	14	14
		Racks/Shelf	4	5	6
		Deelse /Ereener	20	25	30
		Racks/Freezer	20	20	00

Find out more at thermofisher.com/cold



This product is intended for General Laboratory Use. It is the customer's responsibility to ensure that the performance of the product is suitable for customers' specific use or application. © 2019 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific and its subsidiaries unless otherwise specified. BRCS-40RDEGP-EU 1019